

CONTROL YOUR OWN WATER QUALITY!

Models: LB4-021, LB4-031, LB4-061, LB4-101,
 LB4-151, LB4-201

If you are unsure of the microbiological quality of your source water or if you are looking for additional security from your municipal water source, then LUMINOR has the solution in the BLACKCOMB 4.1 series of multi-use UV systems.

UV technology is proven to control microbiological (bacteria & virus) issues in water including *E.coli*, *Cryptosporidium* and *Giardia lamblia*.

Designed for easy, do-it-yourself installation, a BLACKCOMB 4.1 system can be installed on a single tap, or for even greater protection of the home's drinking water, installed at the point-of-entry, thereby treating all the water coming into the home!

Product Features

- Now available with integral lamp life monitor, with both audible and visual indication of lamp life
- Axial flow, 304 stainless steel polished reactors,
- Visual sight port for "lamp-on" verification
- Designed & manufactured to ASME pressure vessel standards
- Flow rates stated at 95% UVT at a dose of 30mJ/cm²
- True gland seal retaining nut with positive stop
- User friendly bayonet style lamp connector (quick ¼ turn removal with no extra tools needed)
- Reliable, industry proven, proprietary low pressure (LP) coated UV lamps with ceramic bases for durability and long life (9,000 hours)
- Constant current electronic controller (one controller for all systems) in a splash proof case, fully potted ballast virtually eliminates common water damage issue
- Audible & visual lamp failure indicators
- Tactile selector button




Point-of-Use (POU)

LB4-02 series, for flow rates of 8 lpm (2 gpm)
LB4-03 series, for flow rates of 11 lpm (3 gpm)

Point-of-Entry (POE)

LB4-06 series, for flow rates of 23 lpm (6 gpm)
LB4-10 series, for flow rates of 41 lpm (11 gpm)
LB4-15 series, for flow rates of 57 lpm (15 gpm)
LB4-20 series, for flow rates of 79 lpm (21 gpm)

Typical POE Installation



Typical POU Installation



BLACKCOMB 4.1 SO - Equipment Specifications

BLACKCOMB (standard-output)						
Model	LB4-021	LB4-031	LB4-061	LB4-101	LB4-151	LB4-201
Flow Rate (30mJ/cm ² @ 95% UVT)	2 GPM	3 GPM	6 GPM	11 GPM	15 GPM	21 GPM
	7.6 lpm	11.4 lpm	22.7 lpm	41 lpm	57 lpm	79 lpm
	0.45 m ³ /hr	0.7 m ³ /hr	1.4 m ³ /hr	2.5 m ³ /hr	3.4 m ³ /hr	4.8 m ³ /hr
Flow Rate (40mJ/cm ² @ 95% UVT)	1.6 GPM	2.4 GPM	4.4 GPM	8.3 GPM	12 GPM	16 GPM
	6.1 lpm	9.1 lpm	17 lpm	31 lpm	45.4 lpm	59 lpm
	0.36 m ³ /hr	0.5 m ³ /hr	1.0 m ³ /hr	1.9 m ³ /hr	2.7 m ³ /hr	3.6 m ³ /hr
Flow Rate (16mJ/cm ² @ 95% UVT)	4 GPM	6 GPM	11 GPM	20 GPM	30 GPM	39 GPM
	15.1 lpm	23 lpm	41 lpm	77 lpm	114 lpm	150 lpm
	0.9 m ³ /hr	1.4 m ³ /hr	2.5 m ³ /hr	4.6 m ³ /hr	6.8 m ³ /hr	8.9 m ³ /hr
Port Size	½" FNPT	½" MNPT	¾" MNPT	¾" MNPT	1" MNPT	1" MNPT
Electrical	90-265V/50-60Hz.					
Plug Type	American, Nema 5/15, 3 wire for all 110V systems, "1" suffix (i.e. LB4-101) European, CEE 7/7, 3 wire for all 230V systems, "2" suffix (i.e. LB4-102) British Standard, BS 1363, 3 wire for all 230V systems, "3" suffix (i.e. LB4-103) Australian/New Zealand, AS/NZ 3112, 3 wire for all 230V systems, "4" suffix (i.e. LB4-104)					
Lamp Watts	8	15	22	39	50	42
Power (Watts)	14	20	30	49	62	51
Maximum Current (amps)	1	1	1	1	1	1
Replacement Lamp	RL-210	RL-290	RL-470	RL-820	RL-999	RL-850
Replacement Sleeve	RQ-210	RQ-290	RQ-470	RQ-820	RQ-999	RQ-850
Replacement Controller	RC-B4.01					
Chamber Material	Polished 304 stainless steel, A249 pressure rated tubing					
Reactor Dimensions	2.5 x 10.3" (6.4 x 26.2cm)	2.5 x 14.3" (6.4 x 36.4cm)	2.5 x 21.3" (6.4 x 54.2cm)	2.5 x 35.2" (6.4 x 89.5cm)	2.5 x 40.0" (6.4 x 101.6cm)	3.5 x 36.1" (8.9 x 91.7cm)
Controller Dimensions	17.2 x 9.2 x 10.2 cm (6.8 x 3.6 x 4")					
Operating Pressure	7-10.3 bar (10-150 psi)					
Operating Water Temp.	2-40° C (36 - 104°F)					
Lamp Change Reminder	YES (4-digit LED display)					
Visual Lamp Out Indicator	YES					
Audible Lamp Out Indicator	YES					
Shipping Weight	2.9 kg (6.3 lbs)	3.6 kg (7.9 lbs)	4.4 kg (9.6 lbs)	6.0 kg (13.2 lbs)	6.5 kg (14.4 lbs)	8.2 kg (18.0 lbs)

Conditions For Use

Your system will provide years of use provided the system is maintained on a regular basis as per the specifications outlined in the Owner's Manual. For the following system to perform as tested, the following water quality parameters must be met.

Parameter	Level
Hardness	< 120 mg/L (7 gpg)
Iron (Fe)	< 0.3 mg/L (ppm)
Manganese (Mn)	< 0.05 mg/L (ppm)
Tannins	< 0.1 mg/L (ppm)
Turbidity	< 1 NTU
Transmittance	> 75% UVT

For levels outside those specified in the table above, please contact the factory for further technical assistance.

Manufacturer's Warranty

REACTORS - Ten (10) year Limited Warranty
ELECTRONICS - Three (3) year Limited Warranty
UV LAMPS - One (1) year Limited Warranty
QUARTZ SLEEVES - One (1) year Limited Warranty



See website for LUMINOR's complete warranty document including conditions and exclusions.

LUMINOR Environmental Inc.
 80 Southgate Drive, Unit 4
 Guelph, Ontario, CANADA
 N1G 4P5

P: (519) 837-3800
 TF: (855) 837-3801
 F: (519) 837-3808
 e-mail: info@luminoruv.com
 web: www.luminoruv.com



EPA Establishment
 #088776-CAN-001

